

**TM 11-6625-1838-15**

**TECHNICAL MANUAL**

**OPERATOR'S, ORGANIZATIONAL, DS, GS,  
AND DEPOT MAINTENANCE MANUAL**

**TEST SET GROUP  
OPTICAL ALIGNMENT  
0Q-62/APS-94D**

---

**HEADQUARTERS, DEPARTMENT OF THE ARMY**

**DECEMBER 1970** ■

TECHNICAL }  
No. 11-6625-1838-15 }

HEADQUARTERS  
DEPARTMENT OF THE ARMY  
WASHINGTON DC, 31 December 1970

Operator's Organizational, Direct Support, General Support and Depot  
Maintenance Manual

TEST SET GROUP, OPTICAL ALIGNMENT OQ-62/APS-94D

|  | Paragraph | Page |
|--|-----------|------|
| <b>CHAPTER 1. INTRODUCTION</b>   |           |      |
| Section I. General   |           |      |
| Scope .....  | 1-1       | 1-1  |
| Indexes of publications .....  | 1-2       | 1-1  |
| Forms and records .....  | 1-3       | 1-1  |
| Reporting of errors .....  | 1-3.1     | 1-3  |
| Differences in models .....  | 1-3.2     |      |
| II. Description and Data   |           |      |
| Purpose and use .....  | 1-4       | 1-1  |
| Technical characteristics .....  | 1-5       | 1-1  |
| Components and dimensions .....  | 1-6       | 1-2  |
| Common names .....   | 1-7       | 1-2  |
| Description of equipment .....   | 1-8       | 1-3  |
| Description of case .....  | 1-9       | 1-3  |
| Description of Test Fixture, Optical Alignment TS-2965/APS-94P .....                   | 1-10      | 1-3  |
| Description of mirror alignment fixture housing .....                                  | 1-11      | 1-3  |
| Description of Telescope, Straight SU-20/APM-214 .....                                 | 1-12      | 1-4  |
| Description of Text Fixture, Optical Alignment TS-2965/APS-94D minor components .....  | 1-13      | 1-4  |
| Lens tool .....  | 1-14      | 1-7  |
| Description of Text Fixture, Optical Alignment TS-2966/APS-94D .....                   | 1-15      | 1-7  |
| Description of lens focus fixture housing .....  | 1-16      | 1-7  |
| Description of compound slide .....  | 1-17      | 1-8  |
| Description of microscope .....  | 1-18      | 1-8  |
| Description of Test Fixture, Optical Alignment TS-2966/APS-94D mirror components ..... | 1-19      | 1-10 |
| Additional equipment required .....  | 1-20      | 1-10 |
| <b>CHAPTER 2. INSTALLATION AND OPERATING INSTRUCTIONS</b>                              |           |      |
| Section I. Service Upon Receipt of Equipment   |           |      |
| Unpacking of Equipment .....   | 2-1       | 2-1  |
| Checking unpacked equipment .....  | 2-2       | 2-3  |
| Installation of equipment .....  | 2-3       | 2-3  |
| Checking the installation .....  | 2-4       | 2-3  |
| II. Operating Instructions   |           |      |
| Operator's controls and indicators .....   | 2-5       | 2-4  |
| Preliminary operating procedures for mirror alignment .....                            | 2-6       | 2-4  |
| Preliminary operating procedures for lens focusing .....                               | 2-7       | 2-5  |
| Preliminary operating procedures for ADAS optical alignment .....                      | 2-8       | 2-6  |
| Operating instructions .....   | 2-9       | 2-7  |
| <b>CHAPTER 3. OPERATOR'S MAINTENANCE INSTRUCTIONS</b>                                  |           |      |
| Section I. Scope, Tools and Equipment  |           |      |
| Scope of operator's maintenance .....  | 3-1       | 3-1  |
| Tools, test equipment, and materials required for operator's maintenance .....         | 3-2       | 3-1  |
| II. Operator's Preventive Maintenance  |           |      |
| General .....  | 3-3       | 3-1  |
| Operator's preventive maintenance and services periods .....                           | 3-4       | 3-1  |

|  | Paragraph | Page |
|--|-----------|------|
| Operator's preventive maintenance checks and services charts .....                 | 3-5       | 3-2  |
| Cleaning.....  | 3-6       | 3-3  |
| Equipment preservation .....   | 3-7       | 3-3  |
| a n d replacement of lamp in Light, Telescope MX-6556/APM-214 .....                | 3-8       | 3-3  |
| <b>CHAPTER 4. ORGANIZATIONAL MAINTENANCE</b>                                       |           |      |
| Section I. General   |           |      |
| Scope of organizational maintenance .....  | 4-1       | 4-1  |
| Tools, test equipment, and materials required for organizational maintenance ..... | 4-2       | 4-1  |
| II. Organizational Preventive Maintenance  |           |      |
| General .....  | 4-3       | 4-1  |
| Organizational preventive maintenance checks and service periods .....             | 4-4       | 4-1  |
| Organizational preventive maintenance checks and services .....                    | 4-5       | 4-1  |
| Cable continuity checks .....  | 4-6       | 4-2  |
| Touchup painting .....   | 4-7       | 4-3  |
| Lubrications.....  | 4-8       | 4-3  |
| <b>CHAPTER 5. FUNCTIONING OF EQUIPMENT</b>   |           |      |
| General .....  | 5-1       | 5-1  |
| Optical mirror alignment .....   | 5-2       | 5-1  |
| Optical lens focus and image magnification adjustments .....                       | 5-3       | 5-2  |
| ADAS optical system alignment .....  | 5-4       | 5-4  |
| <b>CHAPTER 6. DEPOT MAINTENANCE</b>  |           |      |
| Section I. General   |           |      |
| Scope of depot maintenance .....   | 6-1       | 6-1  |
| Tools, test equipment, and materials required for depot maintenance .....          | 6-2       | 6-1  |
| II. Maintenance Procedures   |           |      |
| Overhaul instructions .....  | 6-3       | 6-1  |
| Multiconductor cable repair.....   | 6-4       | 6-1  |
| Disassembly and reassembly of lower transport .....                                | 6-5       | 6-1  |
| Disassembly and reassembly of upper transport .....                                | 6-6       | 6-2  |
| Disassembly and reassembly of image plane light .....                              | 6-7       | 6-2  |
| Removal and replacement sealed-beam lamp in image plane light .....                | 6-8       | 6-4  |
| <b>CHAPTER 7. DEPOT OVERHAUL STANDARDS .....</b>                                   | 7-1       |      |
| <b>8. SHIPMENT, LIMITED STORAGE, AND DEMOLITION TO PREVENT ENEMY USE</b>           |           |      |
| Section I. Shipment and Limited Storage  |           |      |
| Repacking of Equipment   | 8-1       | 8-1  |
| Limited storage.....   | 8-2       | 8-1  |
| II. Demolition to Prevent Enemy Use  |           |      |
| Authority for demolition .....   | 8-3       | 8-2  |
| Methods for destruction .....  | 8-4       | 8-2  |
| Priorities for destruction .....   | 8-5       | 8-2  |
| Destruction of spare parts .....   | 8-6       | 8-2  |
| Reporting of destruction .....   | 8-7       | 8-2  |
| <b>APPENDIX A. REFERENCES .....</b>  | A-1       |      |
| <b>B. MAINTENANCE ALLOCATION CHART .....</b>                                       | B-1       |      |

## LIST OF ILLUSTRATIONS

| Figure No. | Title  | Page        |
|------------|--|-------------|
| 1-1        | Text Fixture, Optical Alignment TS-2965-94D, less minor components                                   | 1 - 4       |
| 1-2        | Mirror alignment fixture housing, front oblique view   | 1 - 5       |
| 1-3        | Mirror alignment fixture housing, rear oblique view  | 1 - 6       |
| 1-4        | Telescope, Straight SU-20/APM-214  | 1-7         |
| 1-5(1)     | Test Fixture, Optical Alignment TS-2965/APS-94D, minor components (sheet 1 of 2)                     | 1-8         |
| 1-5(2)     | Test Fixture, Optical Alignment TS-2965/APS-94D, minor components (sheet 2 of 2) . . . . .           | <b>1-9</b>  |
| 1-6        | Lens tool . . . . .  | 1-10        |
| <b>1-7</b> | Test Fixture, Optical Alignment TS-2966/APS-94D, less minor components                               | <b>1-11</b> |
| 1-8        | Lens focus fixture housing, front oblique view . . . . .   | 1-12        |
| 1-9        | Lens fixture housing, rear oblique view . . . . .  | 1-13        |
| 1-10       | Compound slide   | 1-14        |
| 1-11       | Microscope   | 1-14        |
| 1-12       | Test Fixture, Optical Alignment TS-2966/APS-94D, minor components                                    | 1-15        |
| 2-1        | Case, typical packaging . . . . .  | 2-2         |
| 2-2        | Test Fixture, Optical Alignment TS-2965/APS-94D, pack-aging  | 2-2         |
| 2-3        | Test Fixture, Optical Alignment TS-2966/APS-94D, pack-aging  | 2-3         |
| 2-4        | Installation of RO-352/APS-94D optical housing on Test Fixture, Optical Alignment TS-2965/APS-94D    | 2-6         |
| 2-3        | Installation of EC RO-352/APS-94D optical housing on Test Fixture, Optical Alignment TS-2966/APS-94D | 2-7         |
| 2-6        | Installation of RO-352/APS-94D recorder assembly on Test Fixture, Optical Alignment TS-2966/APS-94D  | 2-8         |
| 5-1        | Optical system light path, light transmission diagram . . . . .                                      | 5-1         |
| 5-2        | Telescope, Straight SU-20/APM-214 position adjustment, light transmission diagram . . . . .          | 5-2         |
| 5-3        | Optical mirror reflection angle adjustments, light transmis-sion diagram . . . . .                   | 5-3         |
| 5-4        | Optical mirror initial position adjustments, light transmission diagram                              | 5-3         |
| 5-5        | Microscope position adjustment, light transmission diagram. . . . .                                  | 5-4         |
| 5-6        | Optical system initial focus adjustment, light transmission dia-gram . . . . .                       | 5-4         |
| 5-7        | Typical image plane projected target group, mask pattern dia-gram . . . . .                          | 5-4         |
| 5-8        | Optical system magnification adjustment, reticle pattern dia-gram                                    | 5-4         |
| 5-9        | ADAS system optical alignment, light transmission diagram . . . . .                                  | 5-5         |
| 6-1        | Lower transport, exploded view   | 6-3         |
| 6-2        | Image plane light, exploded view   | 6-5         |

## LIST OF TABLES

| Table<br>Number | Title   | Page |
|-----------------|---|------|
| 1 - 1           | Dimensions of major components                  | 1-2  |
| 1-2             | Common names                                    | 1-3  |
| 2-1             | Component packaging data                        | 2-1  |
| 2-2             | Operator's controls and indicators              |      |
| 8-1             | Materials for fabrication of shipping box ..... | 8-2  |

# CHAPTER 1

## INTRODUCTION

### Section I. General

#### **1-1. Scope**

Test Set Group, Optical Alignment OQ-62/APS-94D (optical alignment test set) described in this manual is special test equipment for Radar Surveillance Set AN/APS-94D issued for depot only. The optical alignment test set is comprised of Test Fixture, Optical Alignment TS-2965/APS94D (mirror alignment test fixture) and Test Fixture, Optical Alignment TS-2966/APS-94D (Lens focus fixture). Operation, organizational maintenance, and depot maintenance for the aforementioned equipment items are covered in the eight chapters and two appendices that comprise this manual. Common names have been substituted for nomenclatured items. Refer to table 1-2. Direct Support and General Support maintenance is not applicable.

#### **1-2. Indexes of Publications**

**a. DA Pam 310-4.** Refer to the latest issue of DA PAM 310-4 to determine whether there are **new** editions, changes, or additional publications pertaining to the equipment.

**b. DA PAM 310-7.** Refer to the latest issue of DA PAM 310-7 to determine whether there are Modification Work Orders for the equipment.

#### **1-3. Forms and Records**

**a. Reports of Maintenance and Unsatisfactory Equipment.** Maintenance forms, records, and reports which are to be used by maintenance personnel at all maintenance levels are listed in and prescribed by TM 38-750.

**b. Report of Packaging and Handling Deficiencies.** Fill out and forward DD Form 6 (Packaging Improvement Report) as prescribed in AR 700-581 NAVSUPINST 4030.29/AFR 71-13MCO P4030.29A, and DSAR 4145.8.

**c. Discrepancy in Shipment Report (DISREP) (SF 361).** Fill out and forward Discrepancy in Shipment Report (DISREP) (SF 361) as prescribed in AR 55-38/NAVSUPINST 4610.33A/AFR 75-181MCO P4610.19B and DSAR 4500.15.

#### **1-3.1. Reporting of Errors**

The reporting of errors, omissions, and recommendations for improving this manual by the individual user is encouraged. Reports should be submitted on DA Form 2028 (Recommended Changes to Publications and Blank Forms) and forwarded to Commander, U.S. Army Electronics Command, ATTN: DRSEL-MA-Q, Fort Monmouth, NJ 07703.

### Section II. DESCRIPTION AND DATA

#### **1-4. Purpose and Use**

The optical alignment test set optically aligns Recorder-Processor-Viewer, Radar Mapping RO-352/APS-94D Test Fixture. The mirror alignment fixture adjusts RO-352/APS-94D mirror angles and sets optical path length at its maximum. The lens focus fixture reduces the optical path length in the RO-352/APS-94D until focus has been achieved and positions lenses along the optical path to obtain the correct object magnification ratio.

#### **1-5. Technical Characteristics**

##### **a. Optical Alignment Test Set.**

Alignment and focus accuracy.

A resolution of 30 line pairs (minimum) per milliter, covering the distance from the cathode-ray tube (CRT) phosphor surface to the emulsion surface of the recording film

##### **b. Mirror Alignment Fixture.**

###### **(1) Telescope alignment mirror.**

Type of mirror ..... Front surface  
Mirror flatness ..... Flat to 3 fringes per inch at 5893 Angstroms

###### **(2) Lens plane mirror**

Type of mirror ..... Front surface  
Mirror flatness ..... Flat to 3 fringes per inch at 5893 Angstroms

###### **(3) Image plane mask.**

Type of mask ..... Front Surface  
Mask flatness ..... Flat to 9 fringes per inch at 5893 Angstroms  
Mirror flatness ..... Line

###### **(4) Lens plane reticle.**

Type of reticle ..... Circular  
Window flatness ..... Flat to 9 fringes per inch at 5893 Angstroms

###### **(5) Image plane light.**

Type of diffuser ..... Sand blasted surface  
Color of filter ..... Blue  
Type of lamp ..... No. 4505 sealed beam  
Lamp power requirements ..... 28 vdc at 1.8 amperes